



LIKEWOOD®

LET'S
WORK
TOGETHER

LIKEWOOD® CARE & MAINTENANCE

Likewood® decking boasts exceptional durability and is backed by a Limited Lifetime Warranty. To ensure your Likewood® deck maintains its pristine appearance and performance over time, it's essential to adhere to proper maintenance guidelines. Follow these care instructions to uphold warranty coverage:

- **Regular Cleaning:** Remove dirt and debris by periodically washing the deck with an all-surface biodegradable household cleaning product. Utilize a firm, natural fiber cleaning brush for effective cleaning. Avoid using solvent-based or harsh cleaning agents, as they may void the product warranty.
- **Rust Removal:** If rust appears, use a biodegradable toilet bowl cleaner for effective removal. Prior to full application, always test cleaning products on a scrap piece of board or a small inconspicuous area of your Likewood® deck.
- **Protect from Chemicals:** Chemicals present in products like sunblock or insect repellent can lead to discoloration or surface damage. Refrain from applying these products directly onto your Likewood® deck.
- **Prevent Discoloration:** Avoid leaving pool covers, toys, rubber-backed items, tarps, or other non-porous materials on the deck surface for extended periods, as they may cause discoloration.
- **Caution During Installation:** Exercise caution to prevent the transfer of PVC adhesive or similar substances onto the Likewood® deck surface during installation. These materials can cause permanent damage, staining, or discoloration.

By following these care and maintenance guidelines, you can ensure that your Likewood® deck retains its beauty and functionality for years to come, while maintaining warranty coverage.

NOTE: Over time, due to natural weathering, Likewood® PVC decking may appear to lighten depending on the intensity of sunlight exposure and other environmental conditions. As with many plastic materials, static build-up can occur in Likewood® PVC decking. It is a naturally occurring phenomenon that will gradually reduce and nullify over time as elements such as dust and rain are encountered. Although Likewood® PVC decking boasts high heat resistance, all decking surfaces may become hot when exposed to direct sunlight. Lighter colored boards will generally remain cooler than darker colors. Avoid cutting any product on or near Likewood® PVC decking, especially metal, as shavings or sparks could potentially cause damage to the decking material. Prevent the accumulation of jobsite debris or dust (from concrete or masonry products), dirt, mud, etc., on Likewood® PVC decking, as it may lead to damage to the decking surface.

WARNING: Excessive heat build-up from reflecting sunlight, especially reflected by low-emissivity (Low-E) glass, can potentially damage Likewood® PVC Decking and other building materials, since these surface temperatures may far exceed exposure to normal sunlight. Possible damage by such concentrated heat may include warping, sagging, surface discoloration, unusual weathering and increased expansion or contraction.